## **COMFLEX (ALUDUCT)**

## **FLEXIBLE DUCTING**

			MANROSE ALUDUCT	NUDE	INSULATED RO.6
Diameter (mm)	Length (m)	Pack	Order Code	Order Code	Order Code
100	1 3 6	Header Carded Boxed	DCT0357 DCT0328	DCT0367 DCT0409	
125	1 3 6	Header Carded Boxed	DCT0358 DCT0329	DCT0368 DCT0410	
150	1 3 6	Header Carded Boxed	DCT0359 DCT0330	DCT0369 DCT0411	DCT0088 DCT0399
200	3 6	Boxed	DCT0331	DCT0377 DCT0412	DCT0089 DCT0343
250	3 6	Boxed	DCT0332	DCT0370 DCT0413	DCT0400 DCT0344
300	3 6			DCT0380 DCT0414	DCT0401 DCT0402
350	3 6			DCT0415 DCT0416	DCT0403 DCT0404
400	3 6			DCT0417 DCT0418	DCT0405 DCT0406



Nude



Insulated

- **DUCT CORE:** Aluminium foil laminated onto polyester film.
- DUCT SLEEVE: Fire retardant 75µm black low density polyethylene and UV stabilised.
- **DUCT INSULATION:** Polyester R0.6.
- TEMPERATURE RANGE: Maximum: +80°C, Minimum: -10°C.
- COLOUR: Silver with black sleeve.

All 1 metre lengths are packed in bags with header cards, 3 metre aluduct duct is supplied boxed and all other items are supplied in colour coded bags, see page 84 for colour coding.

<sup>2.</sup> No glued/adhesive duct should be installed in a compressed or ovalised state for fear of long term failure.

<sup>3.</sup> Products with the "order code" shown are generally ex. stock lines - other products are available to order.

Should you have an ongoing requirement for an item that is not a standard stock line - PLEASE discuss with us and we will review stocking the item for you.